# Rsm108 9 430ndg Bangladesh

RSM120-9-xxxBNDG RSM108-9-xxxBNDG RSM144-10-xxxBNDG RSM120-10-xxxBNDG RSM108-10-xxxBNDG RSM156-9-xxxBNDG RSM108-9-xxxNDGB RSM108-10-xxxNDGB The detail parameter can be get from the official module datasheet from our website () The Solar PV modules described in this manual are terrestrial used ...

RSM108-9-440N 0 5 10 15 20 25 30 35 40 45 ... RSM1 08 -9 4N 332.8 36.89 11.53 10.76 30.94 Model Type Open Circuit Voltage-Voc (V) Short Circuit Current-Isc (A) M axi mum P ow er Vltg- Vpp Maximum Power Current-Impp (A) M axi mum Power-P x (Wp) Made in China/Malaysia

RSM108-9-415-435NDGB KEY FEATURES Risen"s TOPCon Standard 99% 90% ? ? Risen Energy sales representative for the specific region in which the products 0~+3 % 1500 VDC The m od u le pi ct re is fr r ef ne o y I n dus t ry S a Tolerance Full ...

RSM108-9-415N-440N 108 CELL n-type Module 415-440Wp Power Output Range 1500VDC 22.5% Maximum System Voltage Maximum Efficiency Risen Energy is a leading, global tier 1 manufacturer of high-performance solar photovoltaic products and provider of total business solutions for residential, commercial and utility-scale power generation.

RSM108-9-425NDGB RSM108-9-425NDGB PACKAGING CONFIGURATION 780 936 36 26 40ft(HQ) 1745×1110×1260 216 36 6 20ft N umb er of m odls pr c ntai r Number of modules per pallet Number of pallets per container Packag ing b ox d mes s (L xWH) in m B ox grss wei ght[k] Dimensions of PV Module 30±0.2 M ou ntig hles ± ± 1 1 0 0 ± 1 1 7 2 2 ± 2 A A ...

RSM108-9-415-440BNDG 329.6 36.70 11.49 10.71 30.79 333.4 36.84 11.55 10.76 30.98 Model Type Op en C ircut V oltag- Vc Short Circuit Current-Isc (A) M axi mum P ow er Vltg- Vpp Maximum Power Current-Impp (A) M axi mum Power-P x (Wp) ELECTRICAL DATA (STC) STC: Irradiance 1000 W/m², Cell Temperature 25°C, Air Mass AM1.5 according to EN ...

Web: https://www.worldtheologicaluniversity.co.za